



3GQ-1PLI-D

1.5" LINEAR PENDANT
DIRECT

- Narrow 1.5" aperture with one piece extruded aluminum housing
- Individual or continuous runs available in multiple run configurations
- Direct distribution with multiple lumen output options
- LED system with performance up to 111 lumens per watt
- Extruded acrylic lens with optimal performance and glare control
- Asymmetric optics available
- 1% dimming standard with several driver options



10 DAY QUICKSHIP
Max Order Size: 400'

ORDERING INFORMATION (Options highlighted available for QuickShip)

PROJECT:	<input type="text"/>	TYPE:	<input type="text"/>
CATALOG #:	<input type="text"/>	DATE:	<input type="text"/>

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	VOLTAGE
3GQ-1PLI-D	L250 - LOW OUTPUT (250 LM/FT) ¹	S80 - 83+ CRI	27K - 2700K	UNV - 120/277V 347 - 347V (0-10V ONLY)
	L500 - MEDIUM OUTPUT (500 LM/FT)	H90 - 93+ CRI	30K - 3000K	
	L750 - HIGH OUTPUT (750 LM/FT)		35K - 3500K	
	L1000 - VERY HIGH OUTPUT (1000 LM/FT) ²		40K - 4000K	
	LC___ - CUSTOM OUTPUT (SPECIFY LM/FT)			

DRIVER	LENS OPTION	FINISH	CABLE LENGTH
DIM - 0-10V (STANDARD 100-1%)	FL - FLUSH	WH - WHITE (STANDARD)	60" - 60" (STANDARD)
DHL2 - LUTRON HI-LUME LDE1 (100-1% ECOSYSTEM)	DASY - ASYMMETRIC OPTIC	SV - SILVER	120" - 120"
DALI - DALI (eLdoLED, 100-1%) ³		BK - BLACK (15 DAYS)	
DO1 - 0-10V (eLdoLED, 100-0.1%)			
		All mounting canopies provided in white as standard	

OPTIONS	LENGTH (FEET)
EMC - EMERGENCY CIRCUIT	S - ___' (STRAIGHT RUN) * L - ___'X ___' (L-SHAPE) U - ___'X ___' X ___' (U-SHAPE) R - ___'X ___' (RECTANGLE/SQUARE) T - ___'X ___' (T-SHAPE) X - ___'X ___' (X-SHAPE) CUS - ___ (CUSTOM LAYOUT - PROVIDE DRAWING)
	*Individual units available in 2', 3', 4', 5', 6', and 8' Continuous runs available in 1' increments as standard

¹ L250 (250LM/FT) not available in 2' and 3' lengths. Specify LC400 for 2' and 3' fixture lengths when outputs lower than 500LM/FT are required
² L1000 (1000LM/FT) not available with H90 (93+ CRI)
³ DALI-2 (Type 6) provided as standard. Please consult factory for DALI (Type 8) options

JULY 30, 2020

