



# 3GQ-4PLI-D

3.5" LINEAR PENDANT  
DIRECT



**10 DAY QUICKSHIP**  
Max Order Size: 400'

- 3.5" aperture with one piece extruded aluminum housing
- Individual or continuous runs available in multiple run configurations
- Direct distribution with multiple lumen output options
- LED system with performance up to 136 lumens per watt
- Extruded acrylic lens available in flush, 1" and 2" drop lens options
- Asymmetric optics available
- 1% dimming standard with several driver options

## ORDERING INFORMATION (Options highlighted available for QuickShip)

<b>PROJECT:</b>	<input type="text"/>	<b>TYPE:</b>	<input type="text"/>
<b>CATALOG #:</b>	<input type="text"/>	<b>DATE:</b>	<input type="text"/>

CAT. NO	LUMEN OUTPUT	CRI	COLOR TEMP	VOLTAGE
<b>3GQ-4PLI-D</b>	<b>L250</b> - LOW OUTPUT (250 LM/FT) <sup>1</sup>	<b>S80</b> - 83+ CRI	<b>27K</b> - 2700K	<b>UNV</b> - 120/277V <b>347</b> - 347V (0-10V ONLY)
	<b>L500</b> - MEDIUM OUTPUT (500 LM/FT)	<b>H90</b> - 93+ CRI	<b>30K</b> - 3000K	
	<b>L750</b> - HIGH OUTPUT (750 LM/FT)		<b>35K</b> - 3500K	
	<b>L1000</b> - VERY HIGH OUTPUT (1000 LM/FT) <sup>2</sup>		<b>40K</b> - 4000K	
	<b>LC___</b> - CUSTOM OUTPUT (SPECIFY LM/FT)			

DRIVER	LENS OPTION	FINISH	CABLE LENGTH
<b>DIM</b> - 0-10V (STANDARD 100-1%)	<b>FL</b> - FLUSH	<b>WH</b> - WHITE (STANDARD)	<b>60"</b> - 60" (STANDARD)
<b>DHL2</b> - LUTRON HI-LUME LDE1 (100-1% ECOSYSTEM)	<b>DD1</b> - 1" DROP LENS	<b>SV</b> - SILVER	<b>120"</b> - 120"
<b>DALI</b> - DALI (eLdoLED, 100-1%) <sup>3</sup>	<b>DD2</b> - 2" DROP LENS	<b>BK</b> - BLACK (15 DAYS)	
<b>DO1</b> - 0-10V (eLdoLED, 100-0.1%)	<b>DASY</b> - ASYMMETRIC OPTIC		
		All mounting canopies provided in white as standard	

OPTIONS	LENGTH (FEET)
<b>EMB</b> - INTEGRAL EMERGENCY BATTERY (MIN 4' SECTION)	<b>S</b> - ___' (STRAIGHT RUN) * <b>L</b> - ___'X ___' (L-SHAPE) <b>U</b> - ___'X ___' X ___' (U-SHAPE) <b>R</b> - ___'X ___' (RECTANGLE/SQUARE) <b>T</b> - ___'X ___' (T-SHAPE) <b>X</b> - ___'X ___' (X-SHAPE) <b>CUS</b> - ___ (CUSTOM LAYOUT - PROVIDE DRAWING)
<b>EMC</b> - EMERGENCY CIRCUIT	
*Individual units available in 2', 3', 4', 5', 6', and 8' Continuous runs available in 1' increments as standard	

<sup>1</sup> L250 (250LM/FT) not available in 2' and 3' lengths. Specify LC400 for 2' and 3' fixture lengths when outputs lower than 500LM/FT are required  
<sup>2</sup> L1000 (1000LM/FT) not available with H90 (93+ CRI)  
<sup>3</sup> DALI-2 (Type 6) provided as standard. Please consult factory for DALI (Type 8) options

JULY 30, 2020

