

I-BEAM® Fluorescent High Bay, T5

Cord Set Option:

Add suffix to end of catalog number, specify voltage. All cord sets are 18/3, 6', white unless otherwise noted. Other configurations available, consult factory.

Suffix	Description
CS1W	Straight plug, 120V
CS3W	Twist lock, 120V
CS7W	Straight plug, 277V
CS11W	Twist-lock, 277V
CS25W	Twist-lock, 347V
CS97W	Twist-lock, 480V
CS93W	600V SO white cord, no plug (no voltage required)

Wire Guard Accessories:

Order as a separate catalog number.

Wire guard	Description
WGIBZ14	Standard four-lamp
WGIBZ19	Standard six-lamp
WGIBZ24	Standard eight-lamp

Standard Ballast Configurations:

- 4-lamp: One four-lamp ballast
- 6-lamp: One two-lamp and one four-lamp ballasts
- 8-lamp: Two four-lamp ballasts

Modular Accessories:

Order as a separate catalog number. All cord sets are 18/3, 6', white unless otherwise noted. Must include "IMP" option on fixture.

Suffix	Description
CS1WWMP	Straight plug, 120V
CS3WWMP	Twist lock, 120V
CS7WWMP	Straight plug, 277V
CS11WWMP	Twist-lock, 277V
CS93WWMP	600V SO white cord, no plug (no voltage required)
MSIWMP	Aisle sensor ¹
MSI360WMP	360° sensor ¹

Field-installable Door and Lens Assemblies:²

Lens Type	4-lamp Nomenclature	6-lamp Nomenclature
A12125	DLIBZ14 A12125	DLIBZ19 A12125
ACL	DLIBZ14 ACL	DLIBZ19 ACL
PCL125	DLIBZ14 PCL125	DLIBZ19 PCL125

Notes:

- Must have "WMP" power cord to power fixture. 120/277 voltage only.
- Add WG to nomenclature if wire guard is to be installed in door frame, ex: DLIBZ14A12125WG.

DIMENSIONS

Inches (millimeters). Subject to change without notice.

