

Job: \_\_\_\_\_

**CM1783**


Catalog number

Type: \_\_\_\_\_

Approvals

Lamping choices (lamps are not included as standard)

- CM1783-6F40(120V) (6) 40 watt, Fluorescent, TWIN, 2G11 Base  
Ballast(s): 120V, integral, electronic, H.P.F. Fluorescent.  
Max Operating amps: 2.4
- CM1783-6F40(277V) (6) 40 watt, Fluorescent, TWIN, 2G11 Base  
Ballast(s): 277V, integral, electronic, H.P.F. Fluorescent.  
Max Operating amps: 1.02



- CM1783-8F40(120V) (8) 40 watt, Fluorescent, TWIN, 2G11 Base  
Ballast(s): 120V, integral, electronic, H.P.F. Fluorescent.  
Max Operating amps: 3.2
- CM1783-8F40(277V) (8) 40 watt, Fluorescent, TWIN, 2G11 Base  
Ballast(s): 277V, integral, electronic, H.P.F. Fluorescent.  
Max Operating amps: 1.36

Finish

- PT Painted (Unspecified)

Options

Diffuser Option

None

- AC Opal White Acrylic Diffuser
- IR Impact Resistant Dr Pattern 12 Acrylic
- RL Refractor Lens Lexalite

- WGD Wire Guard: (White Only)

- LRS Lens Retension System

Mounting Option

None

- HH Hook Hung
- HH/CP1 Hook Hung with Nema L5-15P Plug
- HH/CP2 Hook Hung with Nema L7-15P Plug

**This Option is only available in the following combination(s):**

- 6F40(277V)-HH/CP2
- 8F40(277V)-HH/CP2

**Dimensions**

31-1/8" W (width)  
7-7/8" H (height)

**Mounting:**

Mounts to 4" octagonal electrical junction box (by others).

**Mounting note:**

Standard fixture is provided without suspension components, for surface mount. For other mounting, select from mounting options.

**Note:**

Standard fixture is provided with prismatic pattern 12 acrylic diffuser. For other diffusers, select from diffuser options.

**THIS DOCUMENT CONTAINS INFORMATION WHICH IS THE PROPERTY OF VISA LIGHTING, AND MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, DISCLOSED, OR USED FOR DESIGN OR MANUFACTURING PURPOSES WITHOUT THE PRIOR WRITTEN PERMISSION OF VISA LIGHTING.**

- DIM Dimmable integral (fluorescent) ballast  
**This Option is only available in the following combination(s):**  
6F40(120V)-HH-DIM  
6F40(120V)-DIM  
8F40(120V)-DIM  
8F40(120V)-HH-DIM  
6F40(277V)-HH-DIM  
6F40(277V)-DIM  
8F40(277V)-DIM  
8F40(277V)-HH-DIM



Dry

- IEM Integral Emergency battery pack  
**This Option is only available in the following combination(s):**  
6F40(120V)-HH-IEM  
6F40(120V)-IEM  
8F40(120V)-IEM  
8F40(120V)-HH-IEM  
6F40(277V)-HH-IEM  
6F40(277V)-IEM  
8F40(277V)-IEM  
8F40(277V)-HH-IEM

- FU Fusing

- F40L 40W Lamp

- XPS Express 10 Day Shipment

- VAR Variation: Visa Quote Required

**THIS DOCUMENT CONTAINS INFORMATION WHICH IS THE PROPERTY OF VISA LIGHTING, AND MAY NOT, IN WHOLE OR IN PART, BE DUPLICATED, DISCLOSED, OR USED FOR DESIGN OR MANUFACTURING PURPOSES WITHOUT THE PRIOR WRITTEN PERMISSION OF VISA LIGHTING.**