


# Vitis 3

Chandeliers



50 Greene St  
New York NY 10013  
T +1 212 388 1621  
sales@rbw.com



For 2D & 3D drawings of all products, including CAD, Revit and IES files, please visit [rbw.com](http://rbw.com)

Generate Date: Tue Dec 28 2021

**DESCRIPTION**

Designed so that no two installations are exactly alike, Vitis, is a draped modular statement chandelier with endless customizable possibilities. Its flexible, translucent cables accommodate blown-glass orbs at various heights, giving the appearance of lights floating in space.

**MATERIALS**

Blown glass globes, anodized aluminum clasps, woven cord

**COLLECTION NOTES**

Vitis comes with 120 in/ 3048mm cord between globes. Custom length available upon request.  
Power enclosure comes with every order.

**PERFORMANCE**

540 lumens (Ivory); 905 lumens (Smoke)  
Power Consumption 7W  
Luminaire Watts 19.5W  
Per Globe - 28 lm/w (Ivory); 22 lm/w (Smoke)  
90 CRI

**LED LIFESPAN**

50k hours

**PATENT FILE NUMBER**

Patent Number D930,226, 187450, 201912511, 006433652-0001

**CERTIFICATION**

UL Listed  
Suitable for Damp Locations

**SUSPENSION**

White 6" round flat canopy, 6" mud-in (recessed) canopy, and 4 clasps included  
Standard 132" cord between globes. Recommended Hang Height 66", refer to dimensional drawings for more info  
Not field trimmable

Generate Date: Tue Dec 28 2021

**PRODUCT DIMENSIONS**

Dimension will vary base on selected configuration. Please download Tech Pack for details.

**DIMENSIONAL WEIGHT**

55.8 lbs

**YOUR PRODUCT CODE**

**VS-3-IV-CB-AA01-27-120\_TR\_DEX**

## Specification Logic

**GLASS FINISH**

Ivory	IV
Frosted Smoke	SM

**CORD FINISH**

Black Cord	CB
White Cord	CW
Custom Color Cord	CX

**CLASP FINISH**

Natural Anodized	AA01
White Gold Anodized	AA02
Black Anodized	AA04
Custom Powder Coat	PCXX
Polished Chrome	PF13

Generate Date: Tue Dec 28 2021

**COLOR TEMPERATURE**

---


2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

**INPUT / CONTROL / POWER**


---

110-120V Input Triac, 1% dimming	120_TR_DEX
220-240V Input 0-10V, 1% dimming	220_10_DEX
220-240V Input ELV Reverse Phase, 1% dimming	220_ELV_DEX
220-240V Input Triac / Forward Phase, 1% dimming	220_TR_DEX
110-277V Input 0-10V, 0.1% dimming	277_10_DEX
110-277V Input Dali, 0.1% dimming	277_DL_DEX


Drawings




VS-3 Vitis Chandelier Dimension



VS-3 Vitis Chandelier (Condensed High) Dimension



VS-3 Vitis Chandelier (Extra Long) Dimension



VS-3 Vitis Chandelier (Linear) Dimension