


Dimple Sconce

Sconces



50 Greene St
New York NY 10013
T +1 212 388 1621
sales@rbw.com



For 2D & 3D drawings of all products, including CAD, Revit and IES files, please visit rbw.com

Generate Date: Thu Dec 30 2021

DESCRIPTION

Originally designed in collaboration with Sister City, Dimple is a compact and dimmable, flush-mounted sconce that casts a diffuse and soft, atmospheric light. It is cheekily named for the thick, domed circular diffuser embedded into its front face.

MATERIALS

Cast solid glass, aluminum

COLLECTION NOTES

Luminaire lumens listed are for AC input Triac control. DC input are within photometry downloads.

PERFORMANCE

280 lumens (Frosted) | 240 lumens (White) | 120 lumens (Smoke) | 164 lumens (Amber)

Power Consumption 8.5W

Luminaire Watts 7.3W (AC Input)

38 lm/w (Frosted) | 33 lm/w (White) | 17 lm/w (Smoke) | 23 lm/w (Amber)

90 CRI

LED LIFESPAN

50k hour

CERTIFICATION

ADA Compliant

UL Listed

Suitable for Wet Locations

Suitable for Damp Locations

IP20

IP65

**PRODUCT DIMENSIONS**

5" Dia. x 3" Depth

PRODUCT WEIGHT

3 lbs / 1.63 kg

DIMENSIONAL WEIGHT

2 lbs

YOUR PRODUCT CODE

DP-WS- - - - - - -

Specification Logic

GLASS FINISH

White	S1
Smoke	S2
Amber	S3
Frosted	S4

BACKPLATE FINISH

Natural Anodized	AA01
Black Anodized	AA04

COLOR TEMPERATURE

2200K (candle light)	22
2700K (warm white)	27
3000K (soft white)	30
3500K (neutral white)	35

INPUT / CONTROL / POWER

110-120V Input TRIAC Control 10% Dimming	120_TR_LINE
110-120V Input TRIAC / ELV / 0-10V, 1% Dimming	120_TM_DEX
220-240V Input 0-10V, 1% Dimming	220_10_DEX
220-240V Input ELV Reverse Phase, 1% Dimming	220_ELV_DEX
220-240V Input TRIAC / Forward Phase, 1% Dimming	220_TR_DEX
110-277V Input 0-10V, 0.1% Dimming	277_10_DEX
110-277V Input DALI, 0.1% Dimming	277_DL_DEX

IP RATING

IP20 Rated	IP20
IP65 Rated	IP65

Drawings



DP-WS Dimple Sconce Dimension